

Stetra Heat Thermostat (standard)





Stetra Heat Thermostat is a digital device designed to provide precise and reliable control of underfloor heating systems, including remote management via smartphone app. Featuring a simple and intuitive interface, it allows accurate room temperature regulation to optimise comfort and reduce energy consumption. Its compatibility with standard electrical systems and support for daily or weekly programming makes it a practical and versatile solution for a wide range of applications.

Application: Termostato Stetra Heat is designed to efficiently manage underfloor heating in both residential and commercial environments. It can be seamlessly integrated into the heating system and ensures consistent, personalised temperature control based on user preferences. Easy to install on interior walls, the thermostat provides intuitive thermal comfort management while contributing to long-term energy savings.

Stetra Heat Thermostat (color)





Stetra Heat Thermostat (Color) is an advanced digital controller designed to offer precise and reliable management of underfloor heating systems. Equipped with an elegant full-color touchscreen, it enables simple and intuitive temperature control, including remote access via a dedicated smartphone app. With both daily and weekly programming options, it optimizes thermal comfort while minimizing energy consumption. Compatible with standard electrical systems, this thermostat represents a modern, versatile, and functional solution for

Application: Stetra Heat Thermostat (Color) is ideal for controlling underfloor heating in both residential and commercial environments. Easy to install on interior walls, it provides accurate and customizable temperature regulation, ensuring consistent comfort and improved energy savings. App connectivity allows for immediate and user-friendly remote management, adapting easily to the needs of any space or user.

Features	Parameters
Application	for underfloor heating system
Power	AC100- 240V, 50/ 60Hz
Controlled Load	≤ 16A
Mode	Auto Mode (programmable) / Optional Manual Mode
Temperature Accuracy	+/-0.5 °C
Temperature Range	5~60 °C
Programmable Function	5+2/6+1/7 Optional Weekly Schedule
Key Lock Function	SI
Anti-Freeze Function	SI
Memory Function	SI
Temperature Sensor	Two Sensors
Outdoor Floor Sensor Length	3 m
Sensor	NTC
Mobile App	Tuya/Smart Life/Beok Home
Voice Assistant	Google Home/Amazon Alexa
Installation Hole Distance	60mm (suitable for standard European-size mounting boxes)

Dimensions Stetra Heat Thermostat (standard) Dimensions Stetra Heat Thermostat (color)

86x86x12,5mm 86x86x13,3mm



Product Catalogue

79